



Handwritten notes:
 3 units
 2 units
 OK

Standard Efficiency

Model Name	Indoor Unit		FVFC71AXVA RZFC71AXVM	FVFC100AXVA RZFC100AXVM	FVFC140AXVA RZFC140AXVM
Capacity Indication	HP		3.0	4.0	6.0
Rated Cooling Capacity (Min. - Max.)	kW		7.1 (3.2 - 8.0)	10.0 (5.0 - 11.2)	14.0 (6.2 - 15.5)
	Btu/h		24,200 (10,900 - 27,300)	34,100 (17,100 - 38,200)	47,800 (21,200 - 52,900)
Rated Power Consumption	kW		2.33	3.58	5.45
COP	W/W		3.04	2.79	2.57
CSPF	Wh/Wh		4.27	4.12	4.40
DOE Star Rating	*		5*	5*	5*
Power Supply	Φ/V/Hz		1Φ / 220V / 60Hz		
Indoor	Front Panel Color		White		
	Airflow Rate (H/M/L)	CFM	675 / 625 / 530	1,200 / 1,095 / 990	
	Sound Level (H/M/L)	dB (A)	45 / 44 / 40	52 / 49 / 46	53 / 50 / 48
	Dimension (HxWxD)	mm	1,850x600x270	1,850x600x350	
	Weight (Mass)	kg	42	45	48
Outdoor	Casing Color		Ivory White		
	Compressor		Hermetically Sealed Swing Type		
	Sound Level (H)	dB (A)	50	52	54
	Dimension (HxWxD)	mm	615x845x300	695x930x350	990x940x320
	Weight (Mass)	kg	37	40	64
Refrigerant	Type		R32		
	Charge	kg	1.15	0.95	1.90
	Liquid Pipe	mm	Ø 9.5		
Connecting Pipes	Gas Pipe	mm	Ø 15.9		
	Drain	Indoor	Ø 19.05		
		Outdoor	-		
Max. Interunit Piping Length	m	30	50		
Min. Circuit Amps	A	18.5	25.1	32	
Max. Fuse Amps	A	20			